

# MERCATOR



## KITCHEN EQUIPMENT

Refrigeration, Mixers, Food Warmers and Meat  
Slicers, Beverage Dispensers, Granita Machines

# Table of Contents

	The Smart Way to Scale Your Kitchen	<b>3</b>
	Reach-In Refrigerators	<b>4</b>
	Reach-In Freezers	<b>6</b>
	Merchandisers	<b>8</b>
	Undercounter Refrigeration	<b>10</b>
	Prep Tables	<b>12</b>
	Planetary Mixers	<b>14</b>
	Food Warmer	<b>16</b>
	Meat Slicers	<b>17</b>
	Beverage Dispensers	<b>18</b>
	Granita Machines	<b>19</b>

# MERCATOR

At Mercator, we know your kitchen doesn't have time for downtime. That's why we deliver **durable, US-certified commercial equipment** designed to perform under pressure—whether you're cooking, chilling, cleaning, or serving. Backed by **fast delivery, competitive pricing, and reliable warranty programs**, Mercator gives you a one-stop solution to keep operations running smoothly and budgets on track.

<b>Performance You Can Count On</b>	Durable US-certified kitchen equipment engineered for high-volume performance.
<b>Smart Budgets</b>	Highly competitive prices that lower your total cost of ownership.
 <b>Fast Delivery</b>	Strategically stocked inventory to minimize downtime.
<b>Certified &amp; Safe</b>	ETL listed for compliance and peace of mind.
<b>Backed with Confidence</b>	Every product comes with responsive customer support.
<b>One-Stop Solution</b>	From hot kitchens to cold storage to cleanup, Mercator covers your operation end to end.



## Reach-In Refrigerators

Durable refrigerated storage with precise temperature control to keep kitchens running smoothly.

Specification	MR1	MR2
External Dimensions (W x D x H)	29" x 32 1/4" x 82 1/2" (737 x 819 x 2096 mm)	54" x 32 1/4" x 82 1/2" (1372 x 819 x 2096 mm)
Internal Dimensions (W x D x H)	24" x 27" x 60" (610 x 686 x 1524 mm)	49" x 27" x 60" (1245 x 686 x 1524 mm)
Interior Volume	23 Cu Ft (651 L)	46 Cu Ft (1303 L)
Holding Temp. Range	33°F to 40°F (1°C to 4°C)	33°F to 40°F (1°C to 4°C)
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH
Connection Rating Amp	3.6A	6.2A
Refrigerant	R-290	R-290
Doors / Shelves	1 / 3	2 / 6
Net Weight	282 lbs (128 kg)	448 lbs (203 kg)

# Reach-In Refrigerators



## MR1

1 Door Reach-In Refrigerator  
23 Cu. Ft.

### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- Security lock with key
- Casters (4)

### Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (3)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



## MR2

2 Door Reach-In Refrigerator  
48 Cu. Ft.

### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- Security lock with key
- Casters (4)

### Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (6)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



NEMA 5-15p



Intertek



## Reach-In Freezers

Lock in freshness with consistent sub-zero performance built for high-volume kitchens.

Specification	MF1	MF2
<b>External Dimensions (W x D x H)</b>	29" x 32 1/4" x 82 1/2" (737 x 819 x 2096 mm)	54" x 32 1/4" x 82 1/2" (1372 x 819 x 2096 mm)
<b>Internal Dimensions (W x D x H)</b>	24 3/8" x 27" x 60" (619 x 686 x 1524 mm)	49" x 27" x 60" (1245 x 686 x 1524 mm)
<b>Interior Volume</b>	23 Cu Ft (651 L)	46 Cu Ft (1303 L)
<b>Holding Temp. Range</b>	-7°F to 0°F (-22°C to -18°C)	-7°F to 0°F (-22°C to -18°C)
<b>Compressor Power</b>	0.67 HP	1.29 HP
<b>Electrical</b>	115V / 60Hz / 1 PH	115V / 60Hz / 1 PH
<b>Connection Rating Amp</b>	4.2A	8.5A
<b>Refrigerant</b>	R-290	R-290
<b>Doors / Shelves</b>	1 / 3	2 / 6
<b>Net Weight</b>	283 lbs (128 kg)	478 lbs (217 kg)

# Reach-In Freezers

## MF1

1 Door Reach-In Freezer

23 Cu. Ft.



### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- Security lock with key
- Casters (4)

### Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (3)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor

## MF2

2 Door Reach-In Freezer

48 Cu. Ft.



### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- Security lock with key
- Casters (4)

### Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (6)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



NEMA 5-15p



Intertek



Intertek



# Merchandiser Refrigerators

Showcase and sell more with brilliant LED lighting, reliable cooling, and built-in branding space.

Specification	MRM1	MRM2	MRM25
<b>External Dimensions (W x D x H)</b>	27" x 32" x 79 1/2" (686 x 810 x 2019 mm)	54" x 32" x 79 1/2" (1372 x 810 x 2019 mm)	54" x 32" x 79 1/2" (1372 x 810 x 2019 mm)
<b>Internal Dimensions (W x D x H)</b>	26 1/2" x 22" x 52 1/4" (673 x 559 x 1327 mm)	49 1/4" x 26 1/2" x 52 1/4" (1251 x 673 x 1327 mm)	49 1/4" x 26 1/2" x 52 1/4" (1251 x 673 x 1327 mm)
<b>Interior Volume</b>	23 Cu Ft (651 L)	48 Cu Ft (1359 L)	48 Cu Ft (1359 L)
<b>Holding Temp. Range</b>	33°F to 41°F (1°C to 5°C)	33°F to 41°F (1°C to 5°C)	33°F to 41°F (1°C to 5°C)
<b>Electrical</b>	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH
<b>Connection Rating Amp</b>	3.0A	4.5A	4.5A
<b>Refrigerant</b>	R-290 (3.0 oz)	R-290 (3.7 oz)	R-290 (3.7 oz)
<b>Doors / Shelves</b>	1 / 4	2 / 8	2 sliding / 8
<b>Net Weight</b>	325 lbs (148 kg)	490 lbs (223 kg)	490 lbs (223 kg)

# Merchandiser Refrigerators

## MRM1

1 Door Merchandiser Refrigerator  
23 Cu. Ft / Swing Door



### Exterior:

- Constructed of powder coated steel
- Top backlit display panel for customized advertising
- Insulated triple-paned, self-closing glass door
- Digital controls and LED temperature display
- Security lock with key
- Casters (4) and leveling feet (2)
- No drain required

### Interior:

- Walls: powder coated aluminum
- Fully adjustable heavy-duty wire shelves (4)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor

## MRM2

2 Door Merchandiser Refrigerator  
48 Cu. Ft. / Swing Door



### Exterior:

- Constructed of powder coated steel
- Top backlit display panel for customized advertising
- Insulated triple-paned, self-closing glass door
- Digital controls and LED temperature display
- Security lock with key
- Casters (4) and leveling feet (2)
- No drain required

### Interior:

- Walls: powder coated aluminum
- Fully adjustable heavy-duty wire shelves (4)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor

## MRM25

2 Door Merchandiser Refrigerator  
48 Cu. Ft. / Sliding Door



### Exterior:

- Constructed of powder coated steel
- Top backlit display panel for customized advertising
- Insulated triple-paned, self-closing glass door
- Digital controls and LED temperature display
- Security lock with key
- Casters (4) and leveling feet (2)
- No drain required

### Interior:

- Walls: powder coated aluminum
- Fully adjustable heavy-duty wire shelves (4)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



NEMA 5-15p



Intertek Intertek



# Undercounter Refrigeration

Compact cold storage that maximizes workspace and keeps ingredients within reach.

Specification	MUR27	MUR48	MUR60
<b>External Dimensions (W x D x H)</b>	27" x 29 1/2" x 35 1/4" (686 x 749 x 894 mm)	47 1/4" x 29 1/2" x 35 1/4" (1199 x 749 x 894 mm)	60 1/4" x 29 1/2" x 35 1/4" (1529 x 749 x 895 mm)
<b>Internal Dimensions (W x D x H)</b>	22 3/8" x 19 3/4" x 23 1/2" (568 x 502 x 597 mm)	42 5/8" x 19 3/4" x 23 1/2" (1084 x 502 x 597 mm)	55" x 19 3/4" x 23 1/2" (1397 x 502 x 597 mm)
<b>Interior Volume</b>	6 Cu Ft (170 L)	12 Cu Ft (340 L)	17 Cu Ft (481 L)
<b>Holding Temp. Range</b>	32°F to 40°F (0°C to 4°C)	32°F to 40°F (0°C to 4°C)	32°F to 40°F (0°C to 4°C)
<b>Compressor Power</b>	0.17 HP	0.20 HP	0.20 HP
<b>Electrical</b>	115V / 60Hz / 1 PH	115V / 60Hz / 1 PH	115V / 60Hz / 1 PH
<b>Connection Rating Amp / Watts</b>	1.8A / 210W	2.4A / 270W	2.6A / 285W
<b>Refrigerant</b>	R-290	R-290	R-290
<b>Net Weight</b>	154 lbs (70 kg)	209 lbs (95 kg)	282 lbs (128 kg)
<b>Gross Weight</b>	207 lbs (94 kg)	300 lbs (136 kg)	326 lbs (148 kg)

# Undercounter Refrigeration



## MUR27

### 1 Door Undercounter Refrigerator

#### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

#### Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Equipped with 3/4" thick removable polyethylene cutting board
- Topping section holds a variety of food pans up to 6" deep
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



## MUR48

### 2 Door 48" Undercounter Refrigerator

#### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

#### Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Equipped with 3/4" thick removable polyethylene cutting board
- Topping section holds a variety of food pans up to 6" deep
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



## MUR60

### 2 Door 60" Undercounter Refrigerator

#### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

#### Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Equipped with 3/4" thick removable polyethylene cutting board
- Topping section holds a variety of food pans up to 6" deep
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



NEMA 5-15p



Intertek Intertek



## Prep Tables

Streamline prep with chilled topping compartments, full-length cutting boards, and dependable cold holding.

Specification	MPT27	MPT48	MPT60
External Dimensions (WxDxH)	27 1/2" x 29 1/2" x 41 1/2" (699 x 749 x 1054 mm)	46 3/4" x 29 1/2" x 41 1/2" (1187 x 749 x 1054 mm)	60 1/4" x 29 1/2" x 41 1/2" (1530 x 749 x 1054 mm)
Internal Dimensions (W x D x H)	24 1/4" x 19 3/4" x 23 1/2" (616 x 502 x 597 mm)	43" x 19 3/4" x 23 1/2" (1092 x 502 x 597 mm)	56 1/4" x 19 3/4" x 23 1/2" (1429 x 502 x 597 mm)
Interior Volume	6 Cu Ft (170 L)	12 Cu Ft (340 L)	15 Cu Ft (425 L)
Holding Temp. Range	33°F to 40°F (1°C to 4°C)	33°F to 40°F (1°C to 4°C)	33°F to 40°F (1°C to 4°C)
Electrical	0.43 HP	0.56 HP	0.33 HP
Connection Rating Amp / Watts	3.6A / 360W	4.9A / 490W	5.4A / 540W
Refrigerant	R-290	R-290	R-290
Net Weight	176 lbs (80 kg)	253 lbs (115 kg)	306 lbs (139 kg)
Gross Weight	220 lbs (100 kg)	220 lbs (100 kg)	363 lbs (165 kg)



## MPT27

1 Door 27" Refrigerated Prep Table

### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

### Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Equipped with 3/4" thick removable polyethylene cutting board
- Topping section holds a variety of food pans up to 6" deep
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



## MPT48

2 Door 48" Refrigerated Prep Table

### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

### Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Equipped with 3/4" thick removable polyethylene cutting board
- Topping section holds a variety of food pans up to 6" deep
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



## MPT60

2 Door 60" Refrigerated Prep Table

### Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

### Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Equipped with 3/4" thick removable polyethylene cutting board
- Topping section holds a variety of food pans up to 6" deep
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)





## Planetary Mixers

Versatile, gear-driven power for mixing, beating, or whipping—day after day.

Specification	MPM10	MPM20	MPM30
<b>External Dimensions (W x D x H)</b>	15 5/8" x 15 5/8" x 15 5/8"	21 15/16" x 22" x 31 5/16"	22 13/16" x 24 1/8" x 45"
<b>Capacity</b>	10Qt (10L)	20Qt (20L)	30Qt (30L)
<b>Electrical</b>	120 Volts / 60 Hz / 1 PH	120 Volts / 60 Hz / 1 PH	120 Volts / 60 Hz / 1 PH
<b>Connection Rating Amp / Watts</b>	10A / 750 Watts	14A / 1100 Watts	20A / 1500 Watts
<b>Lift Type</b>	Manual	Manual	Manual
<b>RPM</b>	108, 195, 355	108, 195, 355	91, 166, 282
<b>Speed</b>	3 Speed	3 Speed	3 Speed
<b>Transmission Type</b>	Gear-Driven	Gear-Driven	Gear-Driven
<b>Net Weight</b>	79.4 lbs (36 kg)	141.1 lbs (64 kg)	286.6 lbs (130 kg)

# Planetary Mixers



## MPM10

10 Qt. Planetary Stand Mixer

### Special Features:

- Powerful 3-speed motor; gear-driven transmission to withstand daily use
- Durable 10 qt stainless steel bowl; wire bowl guard for added safety
- Includes wire whip, flat beater, and dough hook

- Easy to use with simple on/off buttons and manually operated bowl lift
- 120V, 750W, 1 hp, up to 355 RPM



## MPM20

20 Qt. Planetary Stand Mixer

### Special Features:

- Powerful 3-speed motor; gear-driven transmission to withstand daily use
- Durable 20 qt stainless steel bowl; wire bowl guard for added safety
- Includes wire whip, flat beater, and dough hook

- Easy to use with simple on/off buttons and manually operated bowl lift
- 120V, 1100W, 1 1/2 hp, up to 355 RPM
- Comes with a #12 accessory hub



## MPM30

30 Qt. Planetary Stand Mixer

### Special Features:

- Powerful 3-speed motor; gear-driven transmission to withstand daily use
- Durable 30 qt stainless steel bowl; wire bowl guard for added safety
- Includes wire whip, flat beater, and dough hook

- Easy to use with simple on/off buttons and manually operated bowl lift
- 120V, 1500W, 2 hp, up to 282 RPM
- Comes with a #12 accessory hub



NEMA 5-15p



Intertek Intertek



## Food Warmer

Lightweight, portable heat with even temperature distribution and simple cleanup.

Specification	MFW1
<b>Capacity</b>	6.3 Gal (24L)
<b>Electrical</b>	120V / 60HZ / 1PH
<b>Power Usage</b>	1200 W
<b>Shipping Weight</b>	13 lbs (5.9 kg)
<b>Net Weight</b>	10 lbs (4.5 kg)
<b>Packaging Dimensions (W x D x H)</b>	13 3/8" x 23" x 9 3/8" (340 x 584 x 238 mm)



**MFW1**  
Food Warmer

**Special Features:**

- Electric, light-weight food warmer
- Constructed of corrosion resistant stainless steel
- Adjustable thermostat
- Accommodates all standard size serving pans
- Portable and fits most countertop serving areas





# Meat Slicers

High-torque precision slicers delivering consistent cuts with safety and ease.

Specification	MS10	MS12
<b>Dimensions (W x D x H)</b>	17 7/10" x 16 3/10" x 13 9/10" (500 x 414 x 355mm)	22" x 20" x 18" (554 x 460 x 423mm)
<b>Cut Capacity / Thickness</b>	8" x 6 1/2" / 9/16" (203 x 165mm) / (143 mm)	9" x 7" / 9/16" (229 x 178mm) / (143 mm)
<b>Blade Diameter</b>	10" (254 mm)	12" (305 mm)
<b>Electrical</b>	120V / 50Hz / 1PH	120V / 50Hz / 1PH
<b>Power Usage</b>	0.2HP	0.33HP
<b>Net Weight</b>	44 lbs (20 kg)	55 lbs (25 kg)



**MS10**  
10" Blade Meat Slicer

**Special Features:**

- Constructed of stain resistant cast anodized aluminum
- 10" blade diameter
- "High torque" drive system
- 4 rubberized legs prevent slipping or scratching surfaces



NEMA 5-15p



Intertek Intertek



**MS12**  
12" Blade Meat Slicer

**Special Features:**

- Constructed of stain resistant cast anodized aluminum
- 12" blade diameter
- "High torque" drive system
- 4 rubberized legs prevent slipping or scratching surfaces

# Beverage Dispensers

Durable, efficient cooling for consistently fresh, chilled beverages.

Specification	MRBD1 (Single Bowl)	MRBD2 (Two Bowls)	MRBD3 (Three Bowls)
<b>Capacity per Bowl</b>	3 gal	3 gal	3 gal
<b>Dimensions (W x D x H)</b>	8" x 17" x 24"	16" x 17" x 24"	24" x 17" x 24"
<b>Gross Weight</b>	42 lbs.	69 lbs.	86 lbs.
<b>Power Usage</b>	120V / 60 Hz / 1PH	120V / 60 Hz / 1PH	120V / 60 Hz / 1PH
<b>Watts</b>	300	420	500



**MRBD1**  
1-Bowl Drink Dispenser



**MRBD2**  
2-Bowl Drink Dispenser



**MRBD3**  
3-Bowl Drink Dispenser

## SPECIAL FEATURES:

- Continuous rotary system ensures uniform product consistency
- Durable clear polycarbonate bowls (3-gallon each)
- Stainless steel cooling cylinder, frame, and front panel
- No-drip stainless steel dispensing spout
- Easy push-button operation for efficient service
- Removable drip trays simplify cleaning
- Compact design maximizes counter space
- Engineered for long life with minimal maintenance





## Granita Machines

Reliable freezing performance for smooth, evenly blended drinks.

Specification	MFDM2 (2-Bowl)	MFDM3 (3-Bowl)
<b>Capacity per Bowl</b>	12 L (3.2 gal)	18 L (4.8 gal)
<b>Dimensions (W × D × H)</b>	16" × 21" × 27"	24" × 21" × 27"
<b>Weight</b>	66 lbs (30 kg)	88 lbs (40 kg)
<b>Amps</b>	5.5 A	6.2 A
<b>Voltage</b>	120 V / 650 W / 1PH	120 V / 720 W / 1PH
<b>Construction / Housing</b>	Stainless-Steel + ABS Body	Stainless-Steel + ABS Body



**MFDM2**  
2-Bowl Granita Machine



**MFDM3**  
3-Bowl Granita Machine

### SPECIAL FEATURES:

- Lighted top panel for vibrant product visibility
- Clear, durable polycarbonate bowls
- Stainless steel cooling cylinder, frame, and front panel
- Continuous agitator for smooth, fresh blends
- Powerful 1/3 HP motor for consistent freezing performance
- Removable drip trays simplify cleaning
- Compact design maximizes counter space
- Engineered for long life with minimal maintenance



NEMA 5-15p



Intertek



cETLus



## Granita Machines

Reliable freezing performance for smooth, evenly blended drinks.

Specification	MFDM2 (2-Bowl)	MFDM3 (3-Bowl)
<b>Capacity per Bowl</b>	3 gal	3 gal
<b>Dimensions (W x D x H)</b>	15.7" x 20.5" x 27.2" (381 x 470 x 845 mm)	24" x 18 1/2" x 33 14" (610 x 470 x 845 mm)
<b>Motor</b>	1/3 HP	1/3 HP
<b>Voltage</b>	120 V / 710 W / 1PH	120 V / 980 W / 1PH
<b>Gross Weight</b>	109 lbs (50 kg)	157 lbs (71 kg)



**MFDM2**  
2-Bowl Granita Machine



**MFDM3**  
3-Bowl Granita Machine

### SPECIAL FEATURES:

- Lighted top panel for vibrant product visibility
- Clear, durable polycarbonate bowls
- Stainless steel cooling cylinder, frame, and front panel
- Continuous agitator for smooth, fresh blends
- Powerful 1/3 HP motor for consistent freezing performance
- Removable drip trays simplify cleaning
- Compact design maximizes counter space
- Engineered for long life with minimal maintenance



NEMA 5-15p



Intertek



Intertek



# Engineered for Performance. Priced for Growth.

**MERCATOR**

From **cooking equipment and refrigeration** to cleanup, food prep, and **concession solutions**, Mercator provides a **one-stop source** for durable, ETL-listed food service equipment at highly competitive prices. Backed by fast delivery, strong warranties, and responsive support, Mercator is committed to giving Operations Managers the confidence to focus less on equipment—and more on delivering exceptional dining experiences.

[mercatorfs.com](http://mercatorfs.com)

**Contact Support**

[info@mercatorfs.com](mailto:info@mercatorfs.com) | 954.292.7171

© 2025 MERCATOR